

TL-1 TEST LEAD


- Double Insulation
- 100cm length with Teflon tape insulation
- Max. insulating temperature : 260°C
- CAT III 1000V 20A

TL-2 TEST LEAD


- Double Insulation
- 100cm length with Teflon tape insulation
- CAT III 1000V 10A

TP-01 TEMPERATURE PROBE


- Tests the Temperature of environment
- Probe Connected With K Type Plug
- Thermocouple Index No.: K Type
- Length 1000mm
- Range : -40°C ~ 260°C

TP-02A TEMPERATURE PROBE


- Tests the Temperature of environment
- Probe Connected With K Type Plug
- Thermocouple Index No.: K Type
- Range : -30°C ~ 600°C
- Probe Diameter : 3mm, Probe Length : 80mm
- Cable Length : 1500mm

TP-03A TEMPERATURE PROBE


- Tests the Temperature of environment
- Probe Connected With K Type Plug
- Thermocouple Index No.: K Type
- Range : -30°C ~ 750°C
- Probe Diameter : 3mm, Probe Length : 160mm
- Cable Length : 1500mm

TP-04 TEMPERATURE PROBE


- Tests the Temperature of environment
- Probe Connected With Multimeter Jack
- Range : -40°C ~ 260°C
- Length : 1000mm

RS-232

Features:

- 1.5 Meter Cable with RS – 232 Socket & 5mm Jack for AVM-07 & VB-8205
- 1.5 Meter Cable with RS – 232 Socket & 3.5mm Jack for SL-1352

USB CABLE

Features:

- 1.5 meter Cable with USB 8.5mm jack for AVM-07 & VB-8205

