

**TL-1 TEST LEAD**



- Double Insulation
- 100cm length with Teflon tape insulation
- Max. insulating temperature : 260°C
- CAT III 1000V 20A

**TL-2 TEST LEAD**



- Double Insulation
- 100cm length with Teflon tape insulation
- CAT III 1000V 10A

**TP-01 TEMPERATURE PROBE**



- Tests the Temperature of environment
- Probe Connected With K Type Plug
- Thermocouple Index No.: K Type
- Length 1000mm
- Range : -40°C ~ 260°C

**TP-02A TEMPERATURE PROBE**



- Tests the Temperature of environment
- Probe Connected With K Type Plug
- Thermocouple Index No.: K Type
- Range : -30°C ~ 600°C
- Probe Diameter : 3mm, Probe Length : 80mm
- Cable Length : 1500mm

**TP-03A TEMPERATURE PROBE**



- Tests the Temperature of environment
- Probe Connected With K Type Plug
- Thermocouple Index No.: K Type
- Range : -30°C ~ 750°C
- Probe Diameter : 3mm, Probe Length : 160mm
- Cable Length : 1500mm

**TP-04 TEMPERATURE PROBE**



- Tests the Temperature of environment
- Probe Connected With Multimeter Jack
- Range : -40°C ~ 260°C
- Length : 1000mm

**RS-232**



**Features:**

- 1.5 Meter Cable with RS – 232 Socket & 5mm Jack for AVM-07 & VB-8205
- 1.5 Meter Cable with RS – 232 Socket & 3.5mm Jack for SL-1352

**USB CABLE**



**Features:**

- 1.5 meter Cable with USB 8.5mm jack for AVM-07 & VB-8205

